

EMB-LR1272E

Long Range 868/915 MHz LoRaWAN OEM Module



EMB-LR1272E is a powerful OEM sub-1GHz wireless module featuring the Semtech LoRa® long range modem providing ultra-long range spread spectrum communication and high interference immunity on the 868/915 MHz radio band. It embeds a full LoRaWAN™ Class A and Class C protocols enabling connection to any LoRaWAN™ compliant network infrastructure.

EMB-LR1272E can be configured as an embedded micro system or simple data modem for low power applications in the 868/915 MHz bands. It is based on Semtech SX1272 transceiver coupled with Microchip ATSAMD20/L21 MCU, equipped with up to 256 KBytes of FLASH memory and up to 32 KBytes of SRAM memory.

EMB-LR1272E can communicate with other devices through a wide range of serial interfaces: UART, I2C and SPI ports, several digital and analog I/O ports useful for the management of external devices and interfaces. Thanks to the extremely reduced power consumption (less than 3 µA in sleep mode with RTC running / 1 µA usign XLP sleep) the EMB-LR1272E is a perfect solution to implement long life battery powered devices.

EMB-LR1272E's firmware can be easily developed starting from the Embit SDK, allowing to establish LoRaWAN™ compliant end-nodes or custom point-to-point networks. The Embit evaluation kit (EMB-LR1272E-EVK) contains all the documentation, software and hardware tools to get started with the EMB-LR1272E module.

With the LoRa® disruptive long range wireless technology, the EMB-LR1272E delivers dramatic performance improvements for the AMI, IoT, M2M mobile and consumer markets. It offers a unique network scalability and 10x range extension over existing sub -1GHz solutions.



The LoRa name and associated logo are trademarks of Semtech Corporation or its subsidiaries.



Embit S.r.l.
Via Emilia Est 911
41122 Modena (Italy)
Phone: +39 059 371714
Fax: +39 059 3680498
www.embit.eu | info@embit-eu

Technical Specifications

MCU	Microchip® ATSAMD20Gxx/L21Gxx
Transceiver	Semtech SX1272
Memory	32 KB RAM / 256 KB Flash 8 KB RAM / 64 KB Flash
Frequency	863 ÷ 870 MHz / 902 ÷ 928 MHz
Tx output power	up to +14 dBm up to +19 dBm (opt.)
Rx sensitivity	up to -137 dBm at 300 bps
Data rate	0.3 ÷ 37.5 kbps LoRa® 0.6 ÷ 300 kbps (G)FSK
Interfaces	UART/I2C/SPI/ADC/SWD
Digital I/O	up to 18 lines
Analog I/O	10 ADC channel
Outdoor link range	over 15 km
Supply voltage	1.8 – 3.6 V
Tx current	34 mA @ +14 dBm 125 mA @ +19 dBm
Rx current	12 mA
Sleep Current	≤ 3 µA D20 ≤ 1 µA XLP sleep L21
Antenna	U.FL connector, GSG pcb pads
Dimensions	29,5x22,6x3,5 mm Standard Embit form factor
Connector	SMD Edge Connector
Temperature Range	-40 to +85 °C
Certification	LoRa Alliance certified
Ordering informations	EMB-LR1272E/PC with GSG PADS only EMB-LR1272/ULwith UFL receptacle for external antenna

